


HPC501

Professional balanced phono-feed cable with flexible PVC overall jacket.

Category: Stage Equipment » Proel » Professional bulk cables

Brand: PROEL
Product Code: HPC501



Overview

Professional combined phono-feed cable. Composed by an individual insulated and twisted audio pair + single phase electric power cable. Flexible flame resistant PVC overall jacket. Available models: HPC501: 2 x 0.35 mm² Audio cable + 3 x 1.5 mm² power conductor / HPC502: 2 x 0.35 mm² Audio cable + 3 x 2.5 mm² power conductor. Black color. 100 m wooden reel.

Technical Specifications

Application fields: Audio connections

Conductors: Bare copper

Power: 16 AWG = 3x29x0.25 mm (1,5 mm²)

Signal: 22 AWG = 2x11x0.20 mm (0.35 mm²)

Insulation:

Power: PVC 60 shore Ø 3.0 mm

Signal: PVC HT105 Ø 1.50 mm

Shield: Spiral red copper 4x16x0.12 90%

Jacket: Flexible PVC 60 shore Ø 10.80 mm -Complying with CEI 20-35 (IEC 332.1) regulations

Color: Black

Electrical resistance: 12 Ohm/Km @ 20°C (Power) / 54.5 Ohm/Km @ 20°C (Signal)

Electrical capacitance: 124 pF/m (signal) @ 1 KHz

Operating temperature: -10°C / +60°C

Working tension:

Power: 300/500 V

Signal: < 50 V AC / < 75 V DC

Weight: 182 Kg/Km

Minimum bending radius: 10 x cable section radius

Packaging: 100 m wooden or wood fiber reel