

HPC504

Professional combined phono-feed cable.

Category: Stage Equipment » Proel » Professional bulk cables

Brand: PROEL

Product Code: HPC504



Overview

Professional combined phono-feed cable. Composed by two individual insulated and twisted audio pairs + single phase electric power cable. Flexible flame resistant PVC overall jacket. Section: 2 x 2 x 0.22 mm² Audio cable + 3 x 1.5 mm² power conductor. Black color. 100 m wooden reel.



Technical Specifications

Application fields: Audio connections

Conductors: Bare copper

Power: 16 AWG = 3x29x0.25 mm (1,5 mm²)

Signal: 24 AWG = 7x0.20 mm (0.22 mm²)

Insulation:

Power: PVC 86 shore Ø 3.6 mm

Signal: PVC 86 Ø 1.40 mm

Shield: Braided red copper 0.10 mm > 85%

Jacket: Flexible flame resistant PVC Ø 12mm / Complying with IEC 332-1 (CEI 20-35) regulations

Color: Black

Electrical resistance: 7,4 Ohm/Km @ 20°C (Power) / 80 Ohm/Km @ 20°C (Signal)

Electrical capacitance: 65 pF/m (signal) @ 1 KHz

Operating temperature: -10°C / +60°C

Working tension:

Power: 300/500 V

Signal: < 50 V AC / < 75 V DC

Weight: 225 Kg/Km

Minimum bending radius: 10 x cable section radius

Packaging: 100 m wooden or wood fiber reel