



## SC-FADEmini 6 D

### FEATURES

- USITT DMX-512(1990) Multiplexed Digital Control
- DMX Merge
- Can be linked together to control over 6 channels
- Up to 6 DMX channels and 6 channel control faders
- 6 programmable scenes, ability of up to 100 steps per scene
- Assignable fade setting separately and Master control
- Infrared remote control function
- With a Signal/Power Distribution Box as tension provider and DMX signal converter in the entire system
- Black/White housing optional

### SPECIFICATION

- |   |                          |
|---|--------------------------|
| <input type="checkbox"/> Power Requirement      | 12VDC                    |
| <input type="checkbox"/> Connection             | RJ45                     |
| <input type="checkbox"/> Housing                | PolyCarbonate            |
| <input type="checkbox"/> IP rating              | IP 20                    |
| <input type="checkbox"/> Fire Protection rating | UL 94 V-2                |
| <input type="checkbox"/> Control protocol       | DMX-512 (1990)           |
| <input type="checkbox"/> Listing                | CE certified             |
| <input type="checkbox"/> Operation temperature  | -10 degC to +35 degC     |
| <input type="checkbox"/> Dimensions             | 85(L) x85(W) x 15.5(H)mm |
| <input type="checkbox"/> Weight                 | 150g                     |

### DIMENSIONS

