



SC-Node

FEATURES

- Artnet to DMX/RDM converter
- DMX/RDM to Artnet converter
- Supporting Artnet protocol, USITT DMX-512 (1990) & RDM(E1.20-2006) protocol control
- 16 Subnets x 16 universes = 256 available DMX/RDM universes in a LAN
- XLR connectors for DMX/RDM input/output
- Dip switches for selecting working mode
- Power input of DC5V, 350mA

SPECIFICATION

<input type="checkbox"/> POWER INPUT	DC5V, 350mA
<input type="checkbox"/> HOUSING	Aluminum extrusion
<input type="checkbox"/> LISTING	CE certified
<input type="checkbox"/> DATA IN/OUT	RJ45 connector for Ethernet 5pin XLR connectors for DMX/RDM input/output
<input type="checkbox"/> COMPLIANT PROTOCOLS	Artnet protocol DMX-512 (1990) & RDM(E1.20-2006) control protocol
<input type="checkbox"/> PROTECTING RATING	IP20
<input type="checkbox"/> OPERATING TEMPERATURE	-10 degC to +35 degC
<input type="checkbox"/> STORAGE TEMPERATURE	-20 degC to +70 degC
<input type="checkbox"/> DIMENSIONS	110(L) x 67.5(W) x 42.3(H)mm
<input type="checkbox"/> WEIGHT	185g

DIMENSIONS

