

SC-TOUCH 4 L


FEATURES

- Touch interface, 1Gang (EU version).
- DMX512/PWM output.
 - * SC-TOUCH 4L uses RGB three channels, 2A per channel, 6A in total.
 - * Red is controlled by channel 1, 4, 7...
 - * Green is controlled by channel 2, 5, 8...
 - * Blue is controlled by channel 3, 6, 9...
- Four function menus.
- To record and play back upto 4 scenes and 4 colors.
- To set fadetime for Power on/off and color exchange in the range of 0 to 4s.
- To assign key tone ON/OFF.
- To select input voltage in DC12-24V according to the output loading voltage.
- Online function allows multiple linked SC-TOUCH 4Ls to perform the same Color or Program simultaneously.
- Data backup, function memory and power failure protection.
- White/ Grey/ Black housing optional

SPECIFICATION

<input type="checkbox"/> POWER SUPPLY	DC12-24V
<input type="checkbox"/> LOADING	2A per channel, 6A in total
<input type="checkbox"/> DMX OUT	4Pin Green terminal
<input type="checkbox"/> LINK IN/OUT	4Pin Green terminal
<input type="checkbox"/> PWM OUT & POWER IN	6Pin Green terminal
<input type="checkbox"/> HOUSING	Black Polycarbonate (White, Gray optional)
<input type="checkbox"/> OPERATION TEMPERATURE	0 degC to +35 degC
<input type="checkbox"/> STORAGE TEMPERATURE	-20 degC to +70 degC
<input type="checkbox"/> DIMENSIONS	86(L) x 86(W) x 15.5(H)mm
<input type="checkbox"/> WEIGHT	100g

DIMENSIONS



SC-TOUCH 4 L

SYSTEM CONNECTION

