

LIGHTONE Expression profile LED specs:

Light Source	<ul style="list-style-type: none">◆ LED Qty. : 19PCS◆ Drive Current: 3A
Electrical	<ul style="list-style-type: none">◆ Input Voltage: 100~240 VAC...50/60Hz◆ Max Power: 230W
Control	<ul style="list-style-type: none">◆ On-board: Dimmer◆ Control Protocol: DMX512◆ Control Personality: UNO, Std. W (1CHS, 2CHS)
Optical System	<ul style="list-style-type: none">◆ Dimmer: 0-100%◆ Beam Angle: 26° (19°, 36°, 50°)◆ Color temperature: 3100K
Physical	<ul style="list-style-type: none">◆ Dimensions: 720×380×340mm◆ Weight: 9.6kg (with lens barrel)◆ Housing: Die-cast aluminium◆ Color: Black◆ Fixture Connection: DMX in/out, power in/out◆ Cooling: Forced air
Certification and Safety	<ul style="list-style-type: none">◆ Certification: CE, MET◆ Environment: Dry◆ Operation Temperature: -20°C ~ 45°C
Output	<ul style="list-style-type: none">◆ Max. Flux: 5736lm◆ Peak Intensity: 51142cd◆ Color Rendering: >83Ra